

RADION panic

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Water and dust resistant
- ▶ Sends panic alarms by user for unique identification
- ▶ Single-button or two-button versions, reduces false activations
- ▶ Up to 5 year battery life
- ▶ Supervised for low battery and removal from monitored areas

RADION wireless from Bosch provides the range, scalability and exceptional battery life required to ensure reliable performance and superior quality. Advanced diagnostics and multiple device enrollment options make installation and maintenance simple and cost effective. With a complete line of peripherals, RADION provides the flexibility for virtually any application requirement.

System overview

RADION panic is a wireless, single-button, or two-button transmitter that sends a panic alarm signal to the monitoring system. Each transmitter is programmed with a unique code that allows the monitoring system to recognize individual transmitters.

Functions

RADION panic sends panic code information if one, or both keys are pressed for more than 600 milliseconds.

Water and dust resistant

The housing is designed to resist dust and be resistant to water.

Supervision

RADION panic buttons send supervision check-in transmissions to RADION receivers. When connected to a compatible Bosch control panel featuring user definable supervision for panic buttons, the control panel is alerted if the receiver has not received a check-in transmission from an assigned keyfob within the supervision interval.



Notice

The control panel must be configured to supervise these devices in order to detect the removal of the device from the monitored area.

LED

LED flashes to indicate a signal is sent to your security system

Certifications and approvals

Region	Certificate
US	UL 1023 – Household Burglar Alarm System Units SIA CP-01:2010
Europe	EN50131-1

Region	Certification	
Europe	CE	2004/108/EC EMC Directive (EMC); 2006/95/EC Low-Voltage Directive (LVD); 1999/5/EC Radio equipment and Telecommunications Terminal Equipment (R&TTE); 2011/65/EU Restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)
USA	FCC	Part 15 Security/Remote Control Transmitter 433.42 MHz [433.42 MHz]
Canada	IC	1249A-RWSSFT [-A model numbers]
Brazil	ANATEL	4278-13-1855 [RFPB-SB-A; RFPB-TB-A; RFKF-TB-A]

Installation/configuration notes

Recommended Batteries

The following battery types are recommended for correct operation of your keyfob: Duracell DL2032, Varta CR2032, or Panasonic CR2032.

Parts included

Quantity	Component
1	Panic button
1	Lithium battery (CR2032) coin-cell
1	Installation guide

Technical specifications

Properties

Dimensions	63.7 mm x 35.5 mm x 13.0 mm (2.51 in x 1.40 in x 0.51 in)
------------	--

Power

Power/Voltage	One CR2032 Lithium battery, 3 VDC
Battery Life	Up to 5 years

Environmental Considerations

Temperature	Functional range: -10°C to +49° (+14°F to +120°F) UL only: 0°C to +49°C (+32°F to +120°F) EN 50130-5 Class II only: -10°C to 40°C (+14°F to +104°F)
Environment	Complies with EN50130-5 Class II
Relative Humidity	Up to 93% non-condensing
Frequency	433.42 MHz
Use	Intended for indoor use.

Compatibility

Receivers	B810 (compatible with RFPB-SB-A, and RFPB-TB-A only) RFRC-OPT (compatible with RFPB and RFPB-TB only)
-----------	--

Trademarks

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

RFPB-SB (433.42 MHz)

Wireless, single-button panic. For use in Europe, Africa, and Australia.
Order number **RFPB-SB**

RFPB-SB-A (433.42 MHz)

Wireless, single-button panic. For use in North and South America.
Order number **RFPB-SB-A**

RFPB-SB-CHI (433.42 MHz)

Wireless, single-button panic. For use in China only.
Order number **RFPB-SB-CHI**

RFPB-TB (433.42 MHz)

Wireless, two-button panic. For use in Europe, Africa, and Australia.
Order number **RFPB-TB**

RFPB-TB-A (433.42 MHz)

Wireless, two-button panic fob. For use in North and South America.
Order number **RFPB-TB-A**

RFPB-TB-CHI (433.42 MHz)

Wireless, two-button panic. For use in China only.
Order number **RFPB-TB-CHI**

RFAC-BC-3

Belt clip for the RADION panic and keyfob transmitters. Includes clip-on attachment, 2 screws and secure locking nut, and comes in a 3-pack.
Order number **RFAC-BC-3**

RFAC-LY-10

Necklace lanyard for the RADION panic and keyfob transmitters. 10 lanyards are individually packed in plastic bags.
Order number **RFAC-LY-10**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com