


CM195 Multi Receiver Interface

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Provides increased wireless coverage
- ▶ Multi vendor wireless capable
- ▶ Module Status and Receiver status LEDs
- ▶ Separate tamper input

The CM195 Multi RF Receiver Interface allows up to three wireless RF receivers to be connected to the system simultaneously, providing greater coverage in large or RF unfriendly installations.

System overview

The CM195 is used to provide increased wireless coverage or alternately non Bosch wireless compatibility on the CC110 Solution 64, CC110 Solution 16plus, and CC500 Solution 16i Intrusion Control Panels.. A CM195 will provide connection for up to three wireless receivers.

Functions

Provides increased wireless coverage

Up to three receivers of the same brand and model can be connected to the CM195 and remotely located throughout the installation to increase wireless coverage.

Multi vendor wireless capable

The CM195 is compatible with Bosch DSRF, Secure Wireless, Inovonics, Ness and Crow wireless systems.

Module Status and Receiver status LEDs

The module status LED provides indication that the module is functioning correctly. Three by receiver status LEDs (one per receiver) provide the status of each receiver connected to the system.

Separate tamper input

The separate tamper input allows installation of the module within its own secure enclosure without the need to utilise valuable intrusion inputs to provide cabinet tamper.

Installation/configuration notes

The CM195 is supplied as a PCB module and can be installed in the same cabinet as the main panel or remotely from the panel. The CM195 requires only one module space in the enclosure.

Technical specifications

Power Requirements

Voltage	10.5 to 14 VDC
Current	100 mA MAX
Cable	3 wire connection to control panel INPUT terminal

Environmental Considerations

Temperature	0 to 55 °C
Humidity	5 % to 85 % at 30 °C non condensing

Ordering information

CM195 Multi Receiver Interface
Order number **CM195**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com