NDA-U-RMT Pendant parapet mount

www.boschsecurity.com

BOSCH
Invented for life

▶ Camera installation on parapets, edges of a balcony wall or the side of bridges

▶ Can swivel for easy positioning and servicing

▶ Modular design for fast and easy installation

▶ Weather resistant finish to maintain cosmetic appearance

▶ Vandal resistant design for indoor and outdoor use

The modular camera mounts & accessories are a family of mounts, mounting adapters, pendant interface plates and surveillance cabinets which can be used with a wide range of Bosch cameras. The accessories are easy to install and can be combined to simplify installation in multiple locations whilst retaining the same look and feel.

Functions

Pendant parapet mount

The parapet mount can be used to install cameras on parapets, edges of a balcony wall or the side of bridges. These mounts are fitted to the inside or outside of a suitable wall and can be swiveled for ease of positioning and to make servicing of cameras simpler. An optional flat roof mount adapter (LTC9230/01) can be used for mounting on a flat surface.

The parapet mount can rotate to provide flexibility for a safe and easy installation of the camera on a roof.

Certifications and approvals

Environmental

Salt mist	IEC60068-2-52
Impact	IK10

Parts included

Quantity	Component
1	Roof mount
1	Quick Installation Guide

Technical specifications

Mechanical

Dimensions mounting plate	279 x 346 mm (11 x 13.6 in)
Dimensions arm (W x H)	1069 x 1064 mm (42.1 x 41.9 in)
Weight	8000 g (17.64 lb)

Mechanical

Standard Color	White (RAL 9003)
Construction Material	Aluminum alloy

Base dimensions NDA-U-RMT
Dimensions in mm (inch)

NDA-5030-PIP Pendant interface plate NDE-4/5000
Pendant interface plate for outdoor FLEXIDOME 4000i / 5000i.
Order number **NDA-5030-PIP**

Ordering information

NDA-U-RMT Pendant parapet mount
Universal roof mount for dome cameras, white
Order number **NDA-U-RMT**

Accessories

LTC 9230/01 Roof mount adapter
Flat Roof Mount Adapter for mounting a unit in an upright position on a flat surface.
Order number **LTC 9230/01**